


BUR920000157US1

IN THE CLAIMS

Claims 1-18. (Cancelled).

- Sub*  --19. (New) A method of automatically generating a test environment for an ATE, designed to test a single integrated circuit, the method comprising the steps of:
- mapping the pins of the ATE to a plurality of integrated circuits to create pin data;
 - automatically generating, with a test program generator, a test program and test pattern data for the integrated circuits from pattern data, generic test program rules, and the pin data; and
 - executing the test program to control the ATE.--
- 20. (New) The method of claim 19 further comprising the step of:
- generating functional fail data for each of the integrated circuits.--
- a1* --21. (New) The method of claim 1 wherein the test program includes test vectors and pin assignments for testing the integrated circuits in parallel.--
- 22. (New) An automated test system comprising:
- an integrated circuit tester designed to test a single integrated circuit;
 - a pin data storage area capable of containing pin data for mapping a plurality of integrated circuits to the pins of the integrated circuit tester;
 - a generic program rules storage area; and
 - a test program generator capable of generating a test program from the pin data, test pattern data and generic program rules, the test program capable of controlling the integrated circuit tester for testing the integrated circuits in parallel.--

BUR920000157US1

BT
--23. (New) The automated test system of claim 22 further comprising:

a storage area capable of storing fail data generated during testing for each one of the integrated circuits.--

--24. (New) The automated test system of claim 22 wherein the test program includes test vectors and pin

assignments for testing the integrated circuits in parallel.--

AI
--25. (New) A computer program product comprising:

a computer usable medium having computer readable program code embodied in the medium for automatically generating a test environment for an integrated circuit tester when executed, the computer readable program code including:

computer readable program code that is capable of mapping the pins of the integrated circuit tester to a plurality of integrated circuits to create pin data; and

computer readable program code that is capable of automatically generating, with a test program generator, a test program and test pattern data from the integrated circuits from pattern data, generic test program rules, and the pin data.